



## TECHNICAL DATA SHEET

# KOX Kettenöl

Mineral chain saw oil  $V_{40}= 100 \text{ mm}^2/\text{s}$

### PRODUCT DESCRIPTION

Chain oil with adhesive agent for high-performance motor saws. A very low wear of chains and rails can be guaranteed due to additives, which are improving the lubrication.

### CHARACTERISTICS

Colour / DIN ISO 2049	D 8.0
Appearance	dark brown - black, clear
Density/15°C / DIN EN ISO 12185	0,890 g/cm <sup>3</sup>
Viscosity/40°C / ASTM D 7042	100 mm <sup>2</sup> /s
Viscosity index / ASTM D 2270	110
Flash point (Cleveland) / DIN ISO 2592	200 °C
Pour point / ASTM D 7346	-21 °C
Loading capacity according to Brugger / DIN 51 347	$\geq 36 \text{ N/mm}^2$

### APPLICATION

KOX Kettenöl offers adhesive strength and due to wear preventive additives best lubrication for chain saws. Optimal lubrication even under hard conditions with high performance reserves.

8415KX

03/2021-8415KX-0

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.